

Specifications – Mule 4010 Trans 4x4 “Petrol” 4-person



ENGINE	
Type	Liquid-cooled, 4-stroke 90° V-twin, OHV
Displacement	617 cm ³
Bore and Stroke	76 x 68 mm
Fuel system	Digital Fuel Injection (Mikuni AC34)
Ignition	Digital Electronic
Starting	Electric
DRIVETRAIN	
Transmission	Kawasaki Automatic Power Drive System (KAPS) with reverse, selectable 4WD
Final drive	Gear (Selectable 2WD/4WD), Dual-Mode Differential, Lockable Rear Differential
FRAME	
Suspension:	
Front	Independent, MacPherson strut
Rear	Semi-independent DeDion axle, leaf springs, shocks
Tyre:	
Front	23 x 11.00-10 Tubeless
Rear	23 x 11.00-10 Tubeless
DIMENSIONS	
Overall length	3,305 mm
Overall width	1,486 mm
Overall height	1,925 mm
Wheelbase	2,165 mm
Ground clearance	180 mm
Curb mass	709 kg
Fuel capacity	23.5 litres
Cargo bed load capacity	363 kg (2-person mode), 182 kg (4-person mode)
Cargo box (inside) L x W x H	1,280 x 1,212 x 287 mm (2-person mode) 770 x 1,212 x 287 mm (4-person mode)
Seating capacity	2 or 4
Towing Capacity	545 kgs (trailer + cargo)

The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the vehicle and its performance capabilities but these specifications may not apply to every machine supplied for sale. Patons Event Hire, reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets.

