

Specifications – Mule 610 4x4 “Petrol” 2-person



ENGINE	
Type	Air-cooled, 4-stroke Single, OHV
Displacement	401 cm3
Bore and Stroke	82 x 76 mm
Fuel system	Carburettor: Nikki 6C1026
Ignition	Magneto & transistor
Starting	Electric
DRIVETRAIN	
Transmission	Kawasaki 2 speed, Constantly variable transmission (CVT) with reverse and selectable 4WD
Final drive	Gear (KAF400A: Selectable 2WD/4WD), Dual-Mode differential
FRAME	
Suspension:	
Front	Independent, MacPherson strut
Rear	Unit swing
Tyre:	
Front	24 x 9.00-10 Tubeless
Rear	24 x 11.00-10 Tubeless
DIMENSIONS	
Overall length	2,720 mm
Overall width	1,335 mm
Overall height	1,802 mm
Wheelbase	1,779 mm
Ground clearance	170 mm
Curb mass	460 kg
Fuel capacity	15.5 litres
Cargo bed load capacity	181 kg
Cargo box (inside) L x W x H	1,044 mm x 900 mm x 245 mm
Seating capacity	2
Towing Capacity	420 kg

The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the vehicle and its performance capabilities but these specifications may not apply to every machine supplied for sale. Patons Event Hire, reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets.

